

目录 Contents



晶体管芯片 Transistor Chips

小信号晶体管芯片 Small-Signal Transistor Chips	1
高速开关晶体管芯片 Fast Switching Transistor Chips	2
高压开关晶体管芯片 High-Voltage Switching Transistor Chips	3
功率晶体管芯片 Power Transistor Chips	3
达林顿晶体管芯片 Darlington Transistor Chips	5
数字晶体管芯片 Digital Transistor Chips	5
晶闸管芯片 Thyristor Chips	7

二极管芯片 Diode Chips

高速开关二极管芯片 Fast Switching Diode Chips	8
稳压二极管芯片 Zener Diode Chips	8
小信号肖特基二极管芯片 Small-Signal Schottky Barrier Diode Chips	12
大功率肖特基二极管芯片 Power Schottky Barrier Diode chips	12
镀银点二极管芯片 Silver Bump Diode Chips	13
瞬态电压抑制二极管芯片 TVS Diode Chips	17

集成电路芯片 IC Chips

三端稳压电路芯片 Three-Terminal Voltage Regulator Chips	21
--	----

电力电子器件 Power Electronic Devices

电力电子器件 Power Electronic Devices	21
------------------------------------	----

晶体管芯片 // 小信号晶体管芯片
Transistor Chips Small-Signal Transistor Chips

型号 Type	Ic (mA)	BV _{CEO} (V)	BV _{CBO} (V)	BV _{EBO} (V)	h _{FE}		V _{CE(sat)} (V)	f _T (MHz)	芯片尺寸 Die Size (mm × mm)	晶圆尺寸 Wafer Size
					min	max				
9014SSS	100	50	80	8	60	700	0.3	150	0.26×0.26	5"
9015SSS	-100	-50	-70	-8	60	600	-0.3	100	0.26×0.26	5"
9014S	100	50	80	8	60	700	0.3	150	0.30×0.30	5"
9014SS	100	50	80	8	60	700	0.3	150	0.28×0.28	5"
9014M	100	50	80	8	60	700	0.3	150	0.33×0.33	5"
9014	100	50	80	8	60	700	0.3	150	0.35×0.35	5"
9015S	-100	-50	-70	-8	60	600	-0.3	100	0.30×0.30	5"
9015M	-100	-50	-70	-8	60	600	-0.3	100	0.33×0.33	5"
9015	-100	-50	-70	-8	60	600	-0.3	100	0.35×0.35	5"
2SC5585	500	12	15	6	270	680	0.25	100	0.36×0.36	4"
2SA2018	-500	-12	-15	-6	270	680	-0.25	100	0.36×0.36	4"
9012S	-500	-30	-50	-8	85	400	-0.6	150	0.40×0.40	5"
9013S	500	30	70	6	85	400	0.6	150	0.40×0.40	5"
9013-45V	500	45	70	6	85	400	0.6	150	0.44×0.44	5"
9012	-500	-30	-50	-8	85	400	-0.6	150	0.44×0.44	5"
9013	500	30	70	6	85	400	0.6	150	0.44×0.44	5"
9018	50	20	35	5	100	200	0.5	600	0.32×0.32	5"
5551S	600	160	180	5	100	300	0.5	100	0.42×0.42	5"
5551	600	160	180	5	100	300	0.5	100	0.44×0.44	5"
5401S	-600	-150	-160	-5	100	300	-0.5	100	0.42×0.42	5"
5401	-600	-150	-160	-5	100	300	-0.5	100	0.44×0.44	5"
BC817	500	45	50	6	125	600	0.65	100	0.49×0.49	4", 5"
BC807	-500	-45	-50	-6	125	600	-0.65	100	0.53×0.53	4", 5"
8050A	1000	25	40	5	85	400	0.5	150	0.51×0.51	5"
8550A	-1000	-25	-40	-5	85	400	-0.5	150	0.51×0.51	5"
8050B	1000	25	40	5	85	400	0.5	150	0.51×0.51	5"
8550B	-1000	-25	-40	-5	85	400	-0.5	150	0.51×0.51	5"
8050B-12V	1000	15	25	5	85	400	0.5	100	0.51×0.51	5"
8550B-12V	-1000	-15	-25	-5	85	400	-0.5	100	0.51×0.51	5"
8050	1000	25	40	5	85	400	0.5	150	0.53×0.53	5"
8550	-1000	-25	-40	-5	85	400	-0.5	150	0.53×0.53	5"
8050-12V	1000	15	25	5	85	400	0.5	100	0.53×0.53	5"
8550-12V	-1000	-15	-25	-5	85	400	-0.5	100	0.53×0.53	5"
8050M	1200	25	40	5	85	400	0.5	150	0.60×0.60	5"
8550M	-1200	-25	-40	-5	85	400	-0.5	150	0.60×0.60	5"
8050L	1500	25	40	5	85	400	0.5	150	0.66×0.66	5"
8550L	-1500	-25	-40	-5	85	400	-0.5	150	0.66×0.66	4", 5"
N0.66-80V	600	80	120	6	85	400	0.5	80	0.66×0.66	5"
N0.66-100V	300	100	140	6	85	400	0.5	80	0.66×0.66	5"
A92	-500	-300	-300	-5	60	300	-0.5	50	0.62×0.62	5"
A42	500	300	300	5	60	300	0.5	50	0.62×0.62	5"

晶体管芯片 // 小信号晶体管芯片
Transistor Chips Small-Signal Transistor Chips

型号 Type	Ic (mA)	BV _{CEO} (V)	BV _{CBO} (V)	BV _{EBO} (V)	h _{FE}		V _{CE(sat)} (V)	f _T (MHz)	芯片尺寸 Die Size (mm × mm)	晶圆尺寸 Wafer Size
					min	max				
N0.74	2000	25	40	5	100	400	0.5	100	0.74×0.74	5"
N0.74-50V	800	50	100	5	100	400	0.5	100	0.74×0.74	4", 5"
P0.74	-2000	-25	-40	-5	100	400	-0.5	100	0.74×0.74	5"
P0.74-100V	-300	-100	-120	-5	100	400	-0.5	100	0.74×0.74	5"
N0.8-160V	1000	160	180	6	60	320	0.5	140	0.8×0.8	5"
P0.8-160V	-1000	-160	-180	-6	60	320	-0.5	140	0.8×0.8	5"
N0.89-12V	4000	12	20	6	140	600	0.5	50	0.89×0.89	5"
P0.89-12V	-4000	-12	-20	-6	140	600	-0.5	50	0.89×0.89	5"
N0.89-28V	3000	25	40	6	85	400	0.5	50	0.89×0.89	5"
P0.89-28V	-3000	-25	-40	-6	85	400	-0.5	50	0.89×0.89	5"
D965S	4000	20	40	7	300	1500	1	150	0.89×0.89	5"
8014B	300	20	35	6	100	400	0.3	100	0.35×0.35	5"
8015B	-300	-20	-35	-6	100	400	-0.3	100	0.35×0.35	5"
FMMT491	1000	60	80	5	100	300	0.5	150	0.66×0.66	5"
FMMT591	-1000	-60	-80	-5	100	300	-0.5	150	0.66×0.66	5"
A44	300	400	500	6	50	300	0.3	50	0.89×0.89	4"
A94	-300	-400	-400	-6	50	300	-0.3	50	0.89×0.89	4"
A44S	100	400	500	6	50	300	0.3	50	0.65×0.65	4"
A94S	-100	-400	-400	-6	50	300	-0.3	50	0.65×0.65	4"

晶体管芯片 // 高速开关晶体管芯片
Transistor Chips Fast Switching Transistor Chips

型号 Type	Ic (mA)	BV _{CEO} (V)	BV _{CBO} (V)	BV _{EBO} (V)	h _{FE}		V _{CE(sat)} (V)	f _T (MHz)	芯片尺寸 Die Size (mm × mm)	晶圆尺寸 Wafer Size
					min	max				
3904	200	40	60	6	100	300	0.3	250	0.30×0.30	4", 5"
3906	-200	-40	-40	-5	100	300	-0.4	250	0.30×0.30	4", 5"
3904S	200	40	60	6	100	300	0.3	250	0.26×0.26	5"
3906S	-200	-40	-40	-5	100	300	-0.4	250	0.26×0.26	5"
2907A	-600	-60	-60	-5	100	300	-1.6	250	0.46×0.46	4", 5"
2222A	600	40	75	6	100	300	1	250	0.46×0.46	4", 5"
2907AS	-600	-60	-60	-5	100	300	-1.6	250	0.40×0.40	5"
2222AS	600	40	75	6	100	300	1	250	0.35×0.35	5"
2N4401	600	40	75	6	100	300	0.75	250	0.46×0.46	4"
2N4403	-600	-40	-40	-5.5	100	300	-0.73	250	0.46×0.46	4"
2222AM	600	40	75	6	100	300	1	250	0.42×0.42	4"
2SB1116A	-1000	-60	-80	-6	100	400	-0.3	75	0.89×0.89	4"
2SD1616A	1000	60	120	6	100	400	0.3	100	0.89×0.89	4"

晶体管芯片 // 高压开关晶体管芯片(4")
 Transistor Chips High-Voltage Switching Transistor Chips(4")

型 号 Type	二极管 Diode	Ic (A)	BV _{CEO} (V)	BV _{CBO} (V)	BV _{EBO} (V)	h _{FE}		V _{CE(sat)} (V)	f _T (MHz)	芯片尺寸 Die Size (mm×mm)
						min	max			
13001LX (SN)	N	0.2	480	700	9	15	40	0.5	5	0.82×0.82
13001LX (SN)-420V	N	0.2	410	700	9	15	40	0.5	5	0.82×0.82
HBJN40020A	N	1.5	410	700	7	10	30	0.5	5	1.6×1.6
HBJN40020A (DP)	Y	1.5	410	700	7	10	30	0.5	5	1.6×1.6
BJ198	Y	2	410	700	9	18	30	0.5	5	1.98×1.98
ZJ600P	N	15	430	700	9	25	35	1	4	6.0×6.0
ZJ500P	N	12	430	720	9	20	35		4	5.0×5.0
ZJ190DP	Y	2	410	720	9	15	30	0.5	5	1.9×1.9
ZJ180DP	Y	1.5	410	700	9	15	30	0.5	5	1.8×1.8
KTN70120A	N	8	410	720	9	15	24		4	3.86×3.86
ZJ163P	N	1.5	410	700	9	15	30	0.5	5	1.63×1.63
ZJ173P	N	1.5	410	700	9	15	30	0.5	5	1.73×1.73
ZJ160DP	Y	1.5	410	700	9	15	30	0.5	5	1.60×1.60
ZJ132DP	Y	1.2	410	700	9	15	30	1.4	5	1.32×1.32
GS1420P	N	1.2	410	700	9	15	30	0.6	5	1.42×1.42
GS118P	N	1	410	700	9	15	30	0.5	5	1.18×1.18
13007D	Y	8	410	700	9	15	30	0.6	5	3.3×3.3
13007B	N	8	410	700	9	15	30	0.6	5	3.3×3.3
13005D	Y	4	410	700	9	15	30	0.6	5	2.51×2.51
13005P	N	4	410	700	9	15	30	0.6	5	2.51×2.51
13009G	N	12	410	700	9	25	35		4	4.3×4.3
HBJN40015A	N	1.2	410	700	9	15	30	1.5	5	1.4×1.4
HBJN40015A (DP)	Y	1.2	410	700	9	15	30	1.5	5	1.4×1.4
HBJN40010A	N	1	410	700	9	15	30	0.5	5	1.17×1.17
HBJN40010 (480V)	N	1	480	700	9	15	30	0.5	5	1.17×1.17

 晶体管芯片 // 功率晶体管芯片
 Transistor Chips Power Transistor Chips

型 号 Type	Ic (A)	BV _{CEO} (V)	BV _{CBO} (V)	BV _{EBO} (V)	h _{FE}		V _{CE(sat)} (V)	f _T (MHz)	芯片尺寸 Die Size (mm×mm)	晶圆尺寸 Wafer Size
					min	max				
CJZM718	-2.5	-25	-25	-7.5	300	600	-0.35	150	0.86×0.86	4"
2SB1116Z	-2.5	-20	-20	-6	150	400	-0.35	150	0.86×0.86	4"
N890	2	20~150	30~190	6	100	300	0.5	80	0.89×0.89	4"
P890	-2	-20~-150	-30~-170	-6	100	300	-0.5	80	0.89×0.89	4"
N1150	3	50~150	90~190	6	100	300	0.6	80	1.13×1.13	4"
P1150	-3	-50~-150	-70~-170	-6	100	300	-0.6	80	1.13×1.13	4"
P0.86	-2.5	-20	-20	-6	200	600	-0.35	150	0.86×0.86	5"
P1.0	-3	-20	-20	-6	150	400	-0.35	150	1×1	5"
N1.08-50V	3	50	90	6	100	400	0.5	50	1.08×1.08	5"

 晶体管芯片 // 功率晶体管芯片
 Transistor Chips Power Transistor Chips

型 号 Type	Ic (A)	BV _{CEO} (V)	BV _{CBO} (V)	BV _{EBO} (V)	h _{FE}		V _{CE(sat)} (V)	f _T (MHz)	芯片尺寸 Die Size (mm×mm)	晶圆尺寸 Wafer Size
					min	max				
N1.08-100V	1.5	100	140	6	100	400	0.5	50	1.08×1.08	5"
P1.08-100V	-1.5	-100	-120	-6	100	400	-0.5	50	1.08×1.08	5"
D965	5	20	40	7	300	1500	1	150	1.08×1.08	5"
882M	3	30	60	7	100	400	0.5	50	1.08×1.08	5"
772M	-3	-30	-50	-7	100	400	-0.5	50	1.08×1.08	5"
N1.15-50V	3	50	90	6	100	400	0.5	50	1.13×1.13	5"
N1.15-100V	1.5	100	140	6	100	400	0.5	50	1.13×1.13	5"
N1.15-150V	1	150	190	6	100	400	0.5	50	1.13×1.13	5"
P1.15-50V	-3	-50	-70	-6	100	400	-0.5	50	1.13×1.13	5"
P1.15-100V	-1.5	-100	-120	-6	100	400	-0.5	50	1.13×1.13	5"
P1.15-150V	-1	-150	-170	-6	100	400	-0.5	50	1.13×1.13	5"
N1.4-100V	3	100	120	6	60	250	1.2	10	1.4×1.4	5"
P1.4-100V	-3	-100	-120	-6	60	250	-1.2	10	1.4×1.4	5"
2SB1412	-5	-20	-30	-6	150	350	-1	100	1.40×1.40	4"
2SD2118	5	20	50	6	120	390	1	100	1.40×1.40	4"
N1400	4	60~250	100~300	6	60	320	1.2	15	1.40×1.40	4"
P1400	-4	-60~-250	-80~-270	-6	60	320	-1	15	1.40×1.40	4"
N1800	5	60~150	100~190	6	60	320	1.3	10	1.78×1.78	4"
P1800	-5	-60~-150	-80~-170	-6	60	320	-1.3	10	1.78×1.78	4"
N2000	5	60~250	80~350	6	50	300	2	10	2.00×2.00	4"
P2000	-5	-60~-250	-80~-300	-6	50	300	-2	10	2.00×2.00	4"
N2500	6	60~250	80~350	6	50	300	2	10	2.50×2.50	4"
P2500	-6	-60~-250	-80~-300	-6	50	300	-2	10	2.50×2.50	4"
N3000	8	60~250	80~350	6	50	300	2.5	10	3.00×3.00	4"
P3000	-8	-60~-250	-80~-300	-6	50	300	-2.5	10	3.00×3.00	4"
N3500	10	60~250	80~350	6	50	300	2.5	10	3.45×3.45	4"
P3500	-10	-60~-250	-80~-300	-6	50	300	-2.5	10	3.45×3.45	4"
N4200	12	60~250	80~350	6	50	300	2.5	10	4.20×4.20	4"
P4200	-12	-60~-250	-80~-300	-6	50	300	-2.5	10	4.20×4.20	4"
N5000	15	60~250	80~350	6	55	160	2.5	10	5.00×5.00	4"
P5000	-15	-60~-250	-80~-300	-6	55	160	-2.5	10	5.00×5.00	4"
NSKG1.8	4	100-120	120-150	7	60	200	1	10	1.78×1.78	4"
NSKG2.5	5	100-120	120-150	7	60	200	1.3	10	2.5×2.5	4"
NSKG2.8	6	100-120	120-150	7	60	200	1.5	10	2.8×2.8	4"
NSKG3.0	6	100-120	120-150	7	60	200	1.5	10	3.0×3.0	4"
NSKG3.0-150V	6	150	180	7	60	200	1	10	3.0×3.0	4"
NSKG3.5	8	100-120	120-150	7	60	200	1.5	10	3.45×3.45	4"
NSKG3.5-150V	8	150	180	7	60	200	2	10	3.45×3.45	4"
NSKG4.15	10	100-230V	120-300	7	60	200	2	10	4.15×4.15	4"
NSKG5.0	12	100-230V	120-300	7	60	200	1	10	5.0×5.0	4"

晶体管芯片 // 达林顿晶体管芯片
Transistor Chips // Darlington Transistor Chips

型号 Type	Ic (A)	BV _{CEO} (V)	BV _{CBO} (V)	BV _{EBO} (V)	h _{FE}		V _{CE(sat)} (V)	f _r (MHz)	芯片尺寸 Die Size (mm × mm)	晶圆尺寸 Wafer Size
					min	max				
MMBT28	0.5	100	150	12	10K	45K	1.5	125	0.65 × 0.65	4"
TIPP112S	2	100	150	6	2K	15K	2	10	1.30 × 1.30	4"
TIPP117S	-2	-100	-100	-6	2K	15K	-2	10	1.30 × 1.30	4"
TIPP112	2	100	150	6	2K	15K	1.8	10	1.50 × 1.50	4", 5"
TIPP117	-2	-100	-100	-6	2K	15K	-1.8	10	1.50 × 1.50	4", 5"
TIP112	4	100	150	6	2K	15K	2	10	1.80 × 1.80	4"
TIP117	-4	-100	-100	-6	2K	10K	-2	10	1.80 × 1.80	4"
TIP122	5	100	150	6	2K	15K	2	10	2.14 × 2.14	4"
TIP127	-5	-100	-100	-6	2K	15K	-2	10	2.14 × 2.14	4"
TIP122L	5	100	150	6	2K	15K	2	10	2.28 × 2.28	4"
TIP127L	-5	-100	-100	-6	2K	15K	-2	10	2.28 × 2.28	4"
TIP132	8	100	150	6	2K	15K	2	10	2.8 × 2.8	4"
TIP137	-8	-100	-100	-6	2K	15K	-2	10	2.8 × 2.8	4"
TIP142	10	100	150	6	2K	15K	2.1	10	3.5 × 3.5	4"
TIP147	-10	-100	-100	-6	2K	15K	-2.1	10	3.5 × 3.5	4"
TD425	10	400	500	6	2K	10K	2.5	10	4.25 × 4.25	4"
ND4.5	10	150	200	10	2K	15K	2.5	10	4.5 × 4.5	4"
PD4.5	-10	-150	-160	-10	2K	15K	-2.5	10	4.5 × 4.5	4"
GD500	10	100	150	6	3K	25K	2.5	10	5.00 × 5.00	4"

晶体管芯片 // 数字晶体管芯片 (5")
Transistor Chips // Digital Transistor Chips (5")

型号 Type	Ic (mA)	R ₁ (kΩ)	R ₂ (kΩ)	R ₂ / R ₁	BV _{CEO} (V)	BV _{CBO} (V)	h _{FE}		芯片尺寸 Die Size (mm × mm)
							min	max	
A52P231YW	-100	2.2	2.2	1	-55	-55	30.8	-	0.33 × 0.33
A52P431YW	-100	4.7	4.7	1	-55	-55	25	-	0.33 × 0.33
A52P141YW	-100	10	10	1	-55	-55	77	-	0.33 × 0.33
A52P241YW	-100	22	22	1	-55	-55	77	-	0.33 × 0.33
A52P441YW	-100	47	47	1	-55	-55	77	-	0.33 × 0.33
A52P151YW	-100	100	100	1	-55	-55	92.4	-	0.33 × 0.33
A52P136YW	-100	1	10	10	-55	-55	50.8	-	0.33 × 0.33
A52P234YW	-100	2.2	10	4.7	-55	-55	50.8	-	0.33 × 0.33
A52P237YW	-100	2.2	47	21.4	-55	-55	112	-	0.33 × 0.33
A52P432YW	-100	4.7	10	2.13	-55	-55	46.2	-	0.33 × 0.33
A52P434YW	-100	4.7	22	4.7	-55	-55	77	-	0.33 × 0.33
A52P436YW	-100	4.7	47	10	-55	-55	112	-	0.33 × 0.33
A52P14HYW	-100	10	4.7	0.47	-55	-55	37	-	0.33 × 0.33
A52P144YW	-100	10	47	4.7	-55	-55	77	-	0.33 × 0.33
A52P242YW	-100	22	47	2.14	-55	-55	77	-	0.33 × 0.33

晶体管芯片 // 数字晶体管芯片 (5")
Transistor Chips // Digital Transistor Chips (5")

型号 Type	Ic (mA)	R ₁ (kΩ)	R ₂ (kΩ)	R ₂ / R ₁	BV _{CEO} (V)	BV _{CBO} (V)	h _{FE}		芯片尺寸 Die Size (mm × mm)
							min	max	
A52P44QYW	-100	47	10	0.21	-55	-55	50.8	-	0.33 × 0.33
A52P44HYW	-100	47	22	0.47	-55	-55	77	-	0.33 × 0.33
A52P130YW	-100	1	—	—	-55	-55	120	-	0.33 × 0.33
A52P230YW	-100	2.2	—	—	-55	-55	120	-	0.33 × 0.33
A52P430YW	-100	4.7	—	—	-55	-55	120	-	0.33 × 0.33
A52P140YW	-100	10	—	—	-55	-55	120	-	0.33 × 0.33
A52P240YW	-100	22	—	—	-55	-55	120	-	0.33 × 0.33
A52P44QYW	-100	47	—	—	-55	-55	120	-	0.33 × 0.33
A52P150YW	-100	100	—	—	-55	-55	120	-	0.33 × 0.33
A52P14BYW	-100	0	10	—	-55	-55	46.2	-	0.33 × 0.33
A52P24BYW	-100	0	22	—	-55	-55	77	-	0.33 × 0.33
A52P44BYW	-100	0	47	—	-55	-55	77	-	0.33 × 0.33
A52P15BYW	-100	0	100	—	-55	-55	92.4	-	0.33 × 0.33
A52P131YW	-100	1	1	1	-55	-55	3	-	0.33 × 0.33
C52N231YW	100	2.2	2.2	1	55	55	30.8	-	0.33 × 0.33
C52N431YW	100	4.7	4.7	1	55	55	25	-	0.33 × 0.33
C52N141YW	100	10	10	1	55	55	77	-	0.33 × 0.33
C52N241YW	100	22	22	1	55	55	77	-	0.33 × 0.33
C52N441YW	100	47	47	1	55	55	77	-	0.33 × 0.33
C52N151YW	100	100	100	1	55	55	92.4	-	0.33 × 0.33
C52N136YW	100	1	10	10	55	55	50.8	-	0.33 × 0.33
C52N234YW	100	2.2	10	4.7	55	55	50.8	-	0.33 × 0.33
C52N237YW	100	2.2	47	21.4	55	55	112	-	0.33 × 0.33
C52N432YW	100	4.7	10	2.13	55	55	46.2	-	0.33 × 0.33
C52N434YW	100	4.7	22	4.7	55	55	77	-	0.33 × 0.33
C52N436YW	100	4.7	47	10	55	55	112	-	0.33 × 0.33
C52N14HYW	100	10	4.7	0.47	55	55	37	-	0.33 × 0.33
C52N144YW	100	10	47	4.7	55	55	77	-	0.33 × 0.33
C52N242YW	100	22	47	2.14	55	55	77	-	0.33 × 0.33
C52N44QYW	100	47	10	0.21	55	55	50.8	-	0.33 × 0.33
C52N44HYW	100	47	22	0.47	55	55	77	-	0.33 × 0.33
C52N130YW	100	1	—	—	55	55	120	-	0.33 × 0.33
C52N230YW	100	2.2	—	—	55	55	120	-	0.33 × 0.33
C52N430YW	100	4.7	—	—	55	55	120	-	0.33 × 0.33
C52N140YW	100	10	—	—	55	55	120	-	0.33 × 0.33
C52N240YW	100	22	—	—	55	55	120	-	0.33 × 0.33
C52N44QYW	100	47	—	—	55	55	120	-	0.33 × 0.33
C52N150YW	100	100	—	—	55	55	120	-	0.33 × 0.33
C52N14BYW	100	0	10	—	55	55	46.2	-	0.33 × 0.33
C52N24BYW	100	0	22	—	55	55	77	-	0.33 × 0.33
C52N44BYW	100	0	47	—	55	55	77	-	0.33 × 0.33
C52N15BYW	100	0	100	—	55	55	92.4	-	0.33 × 0.33
C52N131YW	100	1	1	1	55	55	3	-	0.33 × 0.33

晶体管芯片 // 单向可控硅芯片 (4")
Transistor Chips Thyristor Chips (4")

型 号 Type	V _{DRM} (V)	V _{RRM} (V)	I _T (A)	I _{TSM} (A)	I _{GT} (μA) (Max)	V _{TM} (V)	芯片尺寸 Die Size (mm × mm)
JCR0044P	400	—	0.6	6	90	1.7	0.44 × 0.44
JCR0052A (SN)	400	—	0.6	6	150	1.7	0.52 × 0.52
JCR0092BP	600	600	0.8	8	120	1.7	0.92 × 0.92
JCR0110B	600	600	1	10	120	1.7	1.10 × 1.10
JCR0125B	600	600	1.5	15	120	1.7	1.25 × 1.25
JCR0150BG	600	600	2	20	120	1.7	1.50 × 1.50
JCR0150BQ (300V)	300	300	2	20	20000	1.7	1.50 × 1.50
JCR0180BG	600	600	4	40	120	1.7	1.80 × 1.80
JCR0180BQ	600	600	4	40	20000	1.7	1.80 × 1.80
JCR0180BQ (300V)	300	300	4	40	20000	1.7	1.80 × 1.80
JCR0240B	600	600	8	80	20000	1.7	2.40 × 2.40
JCR0250B	600	600	8	80	20000	1.7	2.50 × 2.50
JCR0280B	600	600	12	120	20000	1.7	2.80 × 2.80
JCR0320B	600	600	16	160	20000	1.7	3.20 × 3.20
JCR0350B	600	600	18	180	20000	1.7	3.50 × 3.50

晶体管芯片 // 双向可控硅芯片 (4")
Transistor Chips TRIAC Chips (4")

型 号 Type	V _{DRM} (V)	V _{RRM} (V)	I _T (A)	I _{TSM} (A)	I _{GT} (mA) (Max)				V _{TM} (V)	芯片尺寸 Die Size (mm × mm)
					I	II	III	IV		
JTR0110BG	600	600	0.8	8	5	6	10	20	1.7	1.10 × 1.10
JTR0125BG	600	600	1	10	5	5	10	20	1.7	1.25 × 1.25
JTR0150B4	600	600	2	20	10	10	10	20	1.7	1.50 × 1.50
JTR0160B4	600	600	2	20	10	10	10	20	1.7	1.60 × 1.60
JTR0180B4	600	600	4	40	10	10	10	30	1.7	1.80 × 1.80
JTR0210B4	600	600	4	40	10	10	15	30	1.7	2.10 × 2.10
JTR0230B3	600	600	5	50	10	20	20	—	1.7	2.30 × 2.30
JTR0235B4	600	600	6	60	15	20	30	40	1.7	2.35 × 2.35
JTR0240D4	1200	1200	4	40	25	25	25	75	1.7	2.40 × 2.40
JTR0250B4	600	600	6	60	25	25	25	75	1.7	2.50 × 2.50
JTR0280B4	600	600	8	80	50	50	50	70	1.7	2.80 × 2.80
JTR0320B4	600	600	12	120	30	50	50	70	1.7	3.20 × 3.20
JTR0350B4	600	600	14	140	30	50	50	70	1.7	3.50 × 3.50
JTR0390BG4	600	600	16	160	30	50	50	70	1.7	3.90 × 3.90

二极管芯片 // 高速开关二极管芯片
Diode Chips Fast Switching Diode Chips

型 号 Type	I _F (mA)	V _R (V)	V _{F1} (V)	V _F (V)	I _{R1} (nA)	I _R (μA)	C _T (pF)	t _{rr} (ns)	芯片尺寸 Die Size (mm × mm)	晶圆尺寸 Wafer Size
1SS187SS	100	80	0.65	1	25	1	3	4	0.23 × 0.23	5"
1SS187S	100	80	0.65	1	25	1	3	4	0.26 × 0.26	5"
1SS187S-P	-100	-75	—	-1.2	-25	-5	4	4	0.26 × 0.26	5"
1SS187	100	80	0.65	1	25	1	3	4	0.28 × 0.28	4", 5"
BAS21	200	260	0.65	1	50	—	5	50	0.30 × 0.30	4", 5"
A45 (1SS187共阳) (double, back: +)	-200	-75	—	-1.2	-25	-5	4	4	0.37 × 0.37	5"
C57 (1SS187共阴) (double, back: -)	200	75	—	1.2	25	5	4	4	0.37 × 0.37	5"
BAV99	215	75	0.715	1.25	30	1	3	4	0.28 × 0.28	4", 5"
BAV199	160	75	0.9	1.25	5	—	2	3000	0.28 × 0.28	4", 5"
1504	300	220	0.8	1.48	10	0.02	4	—	0.30 × 0.30	4"

二极管芯片 // 稳压二极管芯片
Diode Chips Zener Diode Chips

型 号 Type	V _Z (V)			I _R (μA)	Z _{ZT} (Ω)	芯片尺寸 Die Size (mm × mm)	晶圆尺寸 Wafer Size
	nom	min	max				
Z5V1M	5.1	4.84	5.36	10	7	0.38 × 0.38	5"
Z5V1L	5.1	4.84	5.36	10	7	0.45 × 0.45	5"
Z12VM	12	11.4	12.6	5	9	0.38 × 0.38	5"
Z12VL	12	11.4	12.6	5	9	0.45 × 0.45	5"
4ZD3V3A	3.3	3.13	3.47	50	9	0.71 × 0.71	4"
4ZD3V6A	3.6	3.43	3.77	50	9	0.71 × 0.71	4"
4ZD3V9A	3.9	3.73	4.07	25	8	0.71 × 0.71	4"
4ZD4V3A	4.3	4.09	4.53	12.5	8	0.71 × 0.71	4"
4ZD4V7A	4.7	4.53	4.9	5	7	0.71 × 0.71	4"
4ZD5V1A	5.1	4.89	5.31	5	6	0.71 × 0.71	4"
4ZD5V6A	5.6	5.37	5.87	5	4.5	0.71 × 0.71	4"

二极管芯片 // 稳压二极管芯片
 Diode Chips // Zener Diode Chips

型 号 Type	V _Z (V)			I _R (μA)	Z _{ZT} (Ω)	芯片尺寸 Die Size (mm × mm)	晶圆尺寸 Wafer Size
	nom	min	max				
4ZD6V2A	6.2	5.91	6.46	5	2	0.71 × 0.71	4"
4ZD6V8A	6.8	6.51	7.13	5	3	0.71 × 0.71	4"
4ZD7V5A	7.5	7.17	7.83	5	3.5	0.71 × 0.71	4"
4ZD8V2A	8.2	7.84	8.62	5	4	0.71 × 0.71	4"
4ZD9V1A	9.1	8.7	9.49	5	4	0.71 × 0.71	4"
4ZD10VA	10	9.6	10.4	5	6	0.71 × 0.71	4"
4ZD11VA	11	10.5	11.5	2.5	7	0.71 × 0.71	4"
4ZD12VA	12	11.5	12.5	2.5	8	0.71 × 0.71	4"
4ZD13VA	13	12.5	14	2.5	9	0.71 × 0.71	4"
4ZD15VA	15	13.9	15.7	2.5	13	0.71 × 0.71	4"
4ZD16VA	16	15.3	17	2.5	14	0.71 × 0.71	4"
4ZD18VA	18	16.9	19.1	2.5	18	0.71 × 0.71	4"
4ZD20VA	20	19.2	21	2.5	20	0.71 × 0.71	4"
4ZD22VA	22	21	23.1	2.5	21	0.71 × 0.71	4"
4ZD24VA	24	23	25.8	2.5	23	0.71 × 0.71	4"
4ZD27VA	27	25.5	28.7	2.5	32	0.71 × 0.71	4"
4ZD30VA	30	28.5	31.7	2.5	36	0.71 × 0.71	4"
4ZD33VA	33	31.6	34.6	2.5	41	0.71 × 0.71	4"
4ZD36VA	36	34.5	37.6	2.5	45	0.71 × 0.71	4"
4ZD39VA	39	37.5	41.2	2.5	55	0.71 × 0.71	4"
4ZD43VA	43	41.4	45.1	0.5	65	0.71 × 0.71	4"
4ZD47VA	47	45.4	49.3	0.5	75	0.71 × 0.71	4"
4ZD51VA	51	49.1	53.5	0.5	90	0.71 × 0.71	4"
4ZD56VA	56	54.1	58.3	0.5	105	0.71 × 0.71	4"
4ZD62VA	62	59.4	65.1	0.5	120	0.71 × 0.71	4"
4ZD68VA	68	65.1	71.2	0.5	145	0.71 × 0.71	4"
4ZD75VA	75	71.7	78.3	0.5	170	0.71 × 0.71	4"
4ZD82VA	82	78.9	86	0.5	190	0.71 × 0.71	4"

 二极管芯片 // 稳压二极管芯片 (5")
 Diode Chips // Zener Diode Chips (5")

型 号 Type	V _Z (V)			I _R (μA)	Z _{ZT} (Ω)	Z _{ZK} (Ω)	芯片尺寸 Die Size (mm × mm)	芯片尺寸 Die Size (mm × mm)	芯片尺寸 Die Size (mm × mm)
	nom	min	max						
BZX84B2V4	2.4	2.35	2.45	50	100	600	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B2V7	2.7	2.64	2.76	20	100	600	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B3V0	3.0	2.94	3.06	10	95	600	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B3V3	3.3	3.23	3.37	5	95	600	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B3V6	3.6	3.52	3.68	5	90	600	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B3V9	3.9	3.82	3.98	3	90	600	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B4V3	4.3	4.21	4.39	3	90	600	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B4V7	4.7	4.6	4.8	3	80	500	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B5V1	5.1	4.99	5.21	2	60	480	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B5V6	5.6	5.48	5.72	1	40	400	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B6V2	6.2	6.07	6.33	3	10	150	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B6V8	6.8	6.66	6.94	2	15	80	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B7V5	7.5	7.35	7.65	1	15	80	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B8V2	8.2	8.03	8.37	0.7	15	80	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B9V1	9.1	8.91	9.29	0.5	15	100	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B10	10	9.8	10.2	0.2	20	150	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B11	11	10.78	11.22	0.1	20	150	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B12	12	11.76	12.24	0.1	25	150	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B13	13	12.74	13.26	0.1	30	170	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B15	15	14.7	15.3	0.05	30	200	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B16	16	15.68	16.32	0.05	40	200	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B18	18	17.64	18.36	0.05	45	225	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B20	20	19.6	20.4	0.05	55	225	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B22	22	21.56	22.44	0.05	55	250	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B24	24	23.52	24.48	0.05	70	250	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B27	27	26.46	27.54	0.05	80	300	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B30	30	29.4	30.6	0.05	80	300	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B33	33	32.34	33.66	0.05	80	325	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B36	36	35.28	36.72	0.05	90	350	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B39	39	38.22	39.78	0.05	130	350	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B43	43	42.14	43.86	0.05	150	375	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B47	47	46.06	47.94	0.05	170	375	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B51	51	49.98	52.02	0.05	180	400	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B56	56	54.88	57.12	0.05	200	425	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B62	62	60.76	63.24	0.05	215	450	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B68	68	66.64	69.36	0.05	240	475	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26
BZX84B75	75	73.5	76.5	0.05	255	500	0.33 × 0.33	0.28 × 0.28	0.26 × 0.26

二极管芯片 // 稳压二极管芯片 (5")
 Diode Chips Zener Diode Chips (5")

型 号 Type	V _Z (V)			I _R (μA)	Z _{ZT} (Ω)	Z _{ZK} (Ω)	芯片尺寸 Die Size (mm × mm)	芯片尺寸 Die Size (mm × mm)	芯片尺寸 Die Size (mm × mm)
	nom	min	max						
BZX84C2V4	2.4	2.2	2.6	50	100	600	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C2V7	2.7	2.5	2.9	20	100	600	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C3V0	3.0	2.8	3.2	10	95	600	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C3V3	3.3	3.1	3.5	5	95	600	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C3V6	3.6	3.4	3.8	5	90	600	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C3V9	3.9	3.7	4.1	3	90	600	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C4V3	4.3	4	4.6	3	90	600	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C4V7	4.7	4.4	5	3	80	500	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C5V1	5.1	4.8	5.4	2	60	480	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C5V6	5.6	5.2	6	1	40	400	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C6V2	6.2	5.8	6.6	3	10	150	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C6V8	6.8	6.4	7.2	2	15	80	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C7V5	7.5	7	7.9	1	15	80	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C8V2	8.2	7.7	8.7	0.7	15	80	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C9V1	9.1	8.5	9.6	0.5	15	100	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C10	10	9.4	10.6	0.2	20	150	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C11	11	10.4	11.6	0.1	20	150	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C12	12	11.4	12.7	0.1	25	150	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C13	13	12.4	14.1	0.1	30	170	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C15	15	13.8	15.6	0.05	30	200	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C16	16	15.3	17.1	0.05	40	200	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C18	18	16.8	19.1	0.05	45	225	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C20	20	18.8	21.2	0.05	55	225	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C22	22	20.8	23.3	0.05	55	250	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C24	24	22.8	25.6	0.05	70	250	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C27	27	25.1	28.9	0.05	80	300	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C30	30	28	32	0.05	80	300	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C33	33	31	35	0.05	80	325	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C36	36	34	38	0.05	90	350	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C39	39	37	41	0.05	130	350	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C43	43	40	46	0.05	150	375	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C47	47	44	50	0.05	170	375	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C51	51	48	54	0.05	180	400	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C56	56	52	60	0.05	200	425	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C62	62	58	66	0.05	215	450	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C68	68	64	72	0.05	240	475	0.33×0.33	0.28×0.28	0.26×0.26
BZX84C75	75	70	79	0.05	255	500	0.33×0.33	0.28×0.28	0.26×0.26

 二极管芯片 // 小信号肖特基二极管芯片
 Diode Chips Small-Signal Schottky Barrier Diode Chips

型 号 Type	I _F (mA)	V _R (V)	V _{F1} (V)	V _F (V)	I _R (μA)	C _T (pF)	t _{rr} (ns)	芯片尺寸 Die Size (mm × mm)	晶圆尺寸 Wafer Size
BAS40	100	42	0.35	1	0.2	5	5	0.23×0.23	4"
BAS70	70	73	0.39	0.95	0.09	2	5	0.23×0.23	4"
BAT54	200	30	0.23	1	2	10	5	0.35×0.35	5"
BAT54S	200	30	0.23	1	2	10	5	0.32×0.32	5"
103AW	350	40	0.37	0.6	5	50	10	0.35×0.35	5"
5817S	1000	20	0.45	0.75	1000	120	—	0.711×0.711	5"
5817	1000	20	0.45	0.75	1000	120	—	0.75×0.75	5"
5818SS	750	30	0.45	—	30	—	—	0.61×0.61	5"
5819	1000	40	0.6	0.9	1000	120	—	0.75×0.75	5"
5819S	1000	40	0.6	0.9	1000	120	—	0.71×0.71	5"
5819SS	750	40	0.6	0.9	1000	120	—	0.61×0.61	5"
5819SSS	500	40	0.55	—	1000	120	—	0.51×0.51	5"
S24N20ALY	750	20	0.47	—	200	—	—	0.61×0.61	5"
S24N40ALY	750	40	0.6	—	500	—	—	0.61×0.61	5"
S28N20ALY	1000	20	0.45	—	100	—	—	0.71×0.71	5"
S28N40ALY	1000	40	0.55	—	50	—	—	0.71×0.71	5"
S28N60ALY	1000	60	0.66	—	100	—	—	0.71×0.71	5"
S30P20ALX	1000	20	0.5	—	30	—	—	0.76×0.76	5"
S30P40ALX	1000	40	0.56	—	10	—	—	0.76×0.76	5"

 二极管芯片 // 大功率肖特基二极管芯片 (5")
 Diode Chips Power Schottky Barrier Diode Chips (5")

型 号 Type	I _F (A)	V _R (V)	I _R (μA)	V _F (V)	T _J (°C)	芯片尺寸 Die Size (mm × mm)
S24N40AYY	0.75	40	1000	0.6	125	0.61×0.61
S26N20AYY	1	20	100	0.46	125	0.66×0.66
S26N40AYY	1	40	100	0.6	125	0.66×0.66
S26N60AYY	1	60	100	0.68	125	0.66×0.66
S28N20AYY	1	20	100	0.45	125	0.71×0.71
S28N40BY	1	40	100	0.6	125	0.71×0.71
S28N60AYY	1	60	100	0.66	125	0.71×0.71
S32N40AYY	1	40	100	0.52	125	0.81×0.81
S32N60AYY	1	60	100	0.62	125	0.81×0.81
S32H100AYY	1	100	5	0.85	175	0.81×0.81
S35N60AYY	2	60	100	0.68	125	0.89×0.89
S40P40AYY	2	40	50	0.54	125	1.016×1.016
S40P60BY	2	60	25	0.68	125	1.016×1.016
S45N20AYY	2	20	100	0.46	125	1.14×1.14
S45P40AYY	2	40	25	0.53	125	1.14×1.14
S45P60AYY	2	60	25	0.63	125	1.14×1.14
S45H60AYY	2	60	2	0.72	175	1.14×1.14
S50P40BY	3	40	50	0.53	125	1.27×1.27
S50P60AYY	3	60	30	0.66	125	1.27×1.27
S55P40BY	3	40	50	0.52	125	1.4×1.4
S55P60AYY	3	60	30	0.63	125	1.4×1.4
S55H60AYY	3	60	2	0.71	175	1.4×1.4
S55H100AYY	3	100	5	0.85	175	1.4×1.4
S60P40AYY	3	40	50	0.53	125	1.52×1.52
S60P60AYY	3	60	50	0.6	125	1.52×1.52
S60H100AYY	3	100	5	0.84	175	1.52×1.52
S66P40AYY	5	40	50	0.54	125	1.67×1.67
S68P40BY	5	40	50	0.52	125	1.73×1.73
S68P60AYY	5	60	50	0.66	125	1.73×1.73
S68H60AYY	5	60	3	0.71	175	1.73×1.73

二极管芯片 // 镀银点开关二极管芯片 (4")
 Diode Chips Silver Bump Switching Diode Chips (4")

型 号 Type	I _F (mA)	V _{RM} (V)	V _R (V)	V _{F1} (V)	V _F (V)	I _{R1} (nA)	I _{R2} (nA)	C _T (pF)	t _{rr} (ns)	芯片尺寸 Die Size (mm × mm)
1N4148SS	200	100	100	0.7	1	25	100	3	4	0.21 × 0.21
1N4148S	200	100	100	0.7	1	25	100	3	4	0.24 × 0.24
BAS21	200	300	250	0.65	1.25	100	-	5	50	0.28 × 0.28

 二极管芯片 // 镀银点稳压二极管芯片 (5")
 Diode Chips Silver Bump Zener Diode Chips (5")

型 号 Type	V _Z (V)			I _R (μA)	Z _{zT} (Ω)	Z _{zK} (Ω)	芯片尺寸 Die Size (mm × mm)
	nom	min	max				
BZX55B2V4	2.4	2.35	2.45	50	85	600	0.31 × 0.31
BZX55B2V7	2.7	2.64	2.76	10	85	600	0.31 × 0.31
BZX55B3V0	3.0	2.94	3.06	4	85	600	0.31 × 0.31
BZX55B3V3	3.3	3.23	3.37	2	85	600	0.31 × 0.31
BZX55B3V6	3.6	3.52	3.68	2	85	600	0.31 × 0.31
BZX55B3V9	3.9	3.82	3.98	2	85	600	0.31 × 0.31
BZX55B4V3	4.3	4.21	4.39	1	75	600	0.31 × 0.31
BZX55B4V7	4.7	4.6	4.8	0.5	60	600	0.31 × 0.31
BZX55B5V1	5.1	4.99	5.21	0.1	35	550	0.31 × 0.31
BZX55B5V6	5.6	5.48	5.72	0.1	25	450	0.31 × 0.31
BZX55B6V2	6.2	6.07	6.33	0.1	10	200	0.31 × 0.31
BZX55B6V8	6.8	6.66	6.94	0.1	8	150	0.31 × 0.31
BZX55B7V5	7.5	7.35	7.65	0.1	7	50	0.31 × 0.31
BZX55B8V2	8.2	8.03	8.37	0.1	7	50	0.31 × 0.31
BZX55B9V1	9.1	8.91	9.29	0.1	10	50	0.31 × 0.31
BZX55B10	10	9.8	10.2	0.1	15	70	0.31 × 0.31
BZX55B11	11	10.78	11.22	0.1	20	70	0.31 × 0.31
BZX55B12	12	11.76	12.24	0.1	20	90	0.31 × 0.31
BZX55B13	13	12.74	13.26	0.1	26	110	0.31 × 0.31
BZX55B15	15	14.7	15.3	0.1	30	110	0.31 × 0.31
BZX55B16	16	15.68	16.32	0.1	40	170	0.31 × 0.31
BZX55B18	18	17.64	18.36	0.1	50	170	0.31 × 0.31
BZX55B20	20	19.6	20.4	0.1	55	220	0.31 × 0.31
BZX55B22	22	21.56	22.44	0.1	55	220	0.31 × 0.31
BZX55B24	24	23.52	24.48	0.1	80	220	0.31 × 0.31
BZX55B27	27	26.46	27.54	0.1	80	220	0.31 × 0.31
BZX55B30	30	29.4	30.6	0.1	80	220	0.31 × 0.31
BZX55B33	33	32.34	33.66	0.1	80	220	0.31 × 0.31
BZX55B36	36	35.28	36.72	0.1	80	220	0.31 × 0.31
BZX55B39	39	38.22	39.78	0.1	90	500	0.31 × 0.31
BZX55B43	43	42.14	43.86	0.1	90	500	0.31 × 0.31
BZX55B47	47	46.06	47.94	0.1	110	600	0.31 × 0.31
BZX55B51	51	49.98	52.02	0.1	125	700	0.31 × 0.31
BZX55B56	56	54.88	57.12	0.1	135	700	0.31 × 0.31
BZX55B62	62	60.76	63.24	0.1	150	1000	0.31 × 0.31
BZX55B68	68	66.64	69.36	0.1	200	1000	0.31 × 0.31
BZX55B75	75	73.5	76.5	0.1	250	1000	0.31 × 0.31

 二极管芯片 // 镀银点肖特基二极管芯片 (4")
 Diode Chips Silver Bump SBD Chips (4")

型 号 Type	I _F (mA)	V _{RM} (V)	V _R (V)	V _{F1} (V)	V _F (V)	I _{R1} (nA)	I _{R2} (nA)	C _T (pF)	t _{rr} (ns)	芯片尺寸 Die Size (mm × mm)
BAS85	200	-	30	0.24	0.8	2000	-	10	-	0.33 × 0.33

 二极管芯片 // 镀银点稳压二极管芯片 (5")
 Diode Chips Silver Bump Zener Diode Chips (5")

型 号 Type	V _Z (V)			I _R (μA)	Z _{zT} (Ω)	Z _{zK} (Ω)	芯片尺寸 Die Size (mm × mm)
	nom	min	max				
BZX55C2V4	2.4	2.28	2.56	50	85	600	0.31 × 0.31
BZX55C2V7	2.7	2.5	2.9	10	85	600	0.31 × 0.31
BZX55C3V0	3.0	2.8	3.2	4	85	600	0.31 × 0.31
BZX55C3V3	3.3	3.1	3.5	2	85	600	0.31 × 0.31
BZX55C3V6	3.6	3.4	3.8	2	85	600	0.31 × 0.31
BZX55C3V9	3.9	3.7	4.1	2	85	600	0.31 × 0.31
BZX55C4V3	4.3	4	4.6	1	75	600	0.31 × 0.31
BZX55C4V7	4.7	4.4	5	0.5	60	600	0.31 × 0.31
BZX55C5V1	5.1	4.8	5.4	0.1	35	550	0.31 × 0.31
BZX55C5V6	5.6	5.2	6	0.1	25	450	0.31 × 0.31
BZX55C6V2	6.2	5.8	6.6	0.1	10	200	0.31 × 0.31
BZX55C6V8	6.8	6.4	7.2	0.1	8	150	0.31 × 0.31
BZX55C7V5	7.5	7	7.9	0.1	7	50	0.31 × 0.31
BZX55C8V2	8.2	7.7	8.7	0.1	7	50	0.31 × 0.31
BZX55C9V1	9.1	8.5	9.6	0.1	10	50	0.31 × 0.31
BZX55C10	10	9.4	10.6	0.1	15	70	0.31 × 0.31
BZX55C11	11	10.4	11.6	0.1	20	70	0.31 × 0.31
BZX55C12	12	11.4	12.7	0.1	20	90	0.31 × 0.31
BZX55C13	13	12.4	14.1	0.1	26	110	0.31 × 0.31
BZX55C15	15	13.8	15.6	0.1	30	110	0.31 × 0.31
BZX55C16	16	15.3	17.1	0.1	40	170	0.31 × 0.31
BZX55C18	18	16.8	19.1	0.1	50	170	0.31 × 0.31
BZX55C20	20	18.8	21.2	0.1	55	220	0.31 × 0.31
BZX55C22	22	20.8	23.3	0.1	55	220	0.31 × 0.31
BZX55C24	24	22.8	25.6	0.1	80	220	0.31 × 0.31
BZX55C27	27	25.1	28.9	0.1	80	220	0.31 × 0.31
BZX55C30	30	28	32	0.1	80	220	0.31 × 0.31
BZX55C33	33	31	35	0.1	80	220	0.31 × 0.31
BZX55C36	36	34	38	0.1	80	220	0.31 × 0.31
BZX55C39	39	37	41	0.1	90	500	0.31 × 0.31
BZX55C43	43	40	46	0.1	90	500	0.31 × 0.31
BZX55C47	47	44	50	0.1	110	600	0.31 × 0.31
BZX55C51	51	48	54	0.1	125	700	0.31 × 0.31
BZX55C56	56	52	60	0.1	135	700	0.31 × 0.31
BZX55C62	62	58	66	0.1	150	1000	0.31 × 0.31
BZX55C68	68	64	72	0.1	200	1000	0.31 × 0.31
BZX55C75	75	70	79	0.1	250	1000	0.31 × 0.31

二极管芯片 // 镀银点稳压二极管芯片 (5")
 Diode Chips Silver Bump Zener Diode Chips (5")

型 号 Type	V _Z (V)			I _R (μA)	Z _{ZT} (Ω)	Z _{ZK} (Ω)	芯片尺寸 Die Size (mm × mm)
	nom	min	max				
BGN4733S	5.1	4.84	5.36	10	7	550	0.36 × 0.36
BLN4733T	5.1	4.84	5.36	10	7	550	0.43 × 0.43
BGN4742S	12	11.4	12.6	5	9	700	0.36 × 0.36
BLN4742T	12	11.4	12.6	5	9	700	0.43 × 0.43

 二极管芯片 // 镀银点稳压二极管芯片 (5")
 Diode Chips Silver Bump Zener Diode Chips (5")

型 号 Type	V _Z (V)			I _R (μA)	Z _{ZT} (Ω)	Z _{ZK} (Ω)	芯片尺寸 Die Size (mm × mm)
	nom	min	max				
BZX79B2V4	2.4	2.35	2.45	50	100	600	0.31 × 0.31
BZX79B2V7	2.7	2.64	2.76	20	100	600	0.31 × 0.31
BZX79B3V0	3.0	2.94	3.06	10	95	600	0.31 × 0.31
BZX79B3V3	3.3	3.23	3.37	5	95	600	0.31 × 0.31
BZX79B3V6	3.6	3.52	3.68	5	90	600	0.31 × 0.31
BZX79B3V9	3.9	3.82	3.98	3	90	600	0.31 × 0.31
BZX79B4V3	4.3	4.21	4.39	3	90	600	0.31 × 0.31
BZX79B4V7	4.7	4.6	4.8	3	80	500	0.31 × 0.31
BZX79B5V1	5.1	4.99	5.21	2	60	480	0.31 × 0.31
BZX79B5V6	5.6	5.48	5.72	1	40	400	0.31 × 0.31
BZX79B6V2	6.2	6.07	6.33	3	10	150	0.31 × 0.31
BZX79B6V8	6.8	6.66	6.94	2	15	80	0.31 × 0.31
BZX79B7V5	7.5	7.35	7.65	1	15	80	0.31 × 0.31
BZX79B8V2	8.2	8.03	8.37	0.7	15	80	0.31 × 0.31
BZX79B9V1	9.1	8.91	9.29	0.5	15	100	0.31 × 0.31
BZX79B10	10	9.8	10.2	0.2	20	150	0.31 × 0.31
BZX79B11	11	10.78	11.22	0.1	20	150	0.31 × 0.31
BZX79B12	12	11.76	12.24	0.1	25	150	0.31 × 0.31
BZX79B13	13	12.74	13.26	0.1	30	170	0.31 × 0.31
BZX79B15	15	14.7	15.3	0.05	30	200	0.31 × 0.31
BZX79B16	16	15.68	16.32	0.05	40	200	0.31 × 0.31
BZX79B18	18	17.64	18.36	0.05	45	225	0.31 × 0.31
BZX79B20	20	19.6	20.4	0.05	55	225	0.31 × 0.31
BZX79B22	22	21.56	22.44	0.05	55	250	0.31 × 0.31
BZX79B24	24	23.52	24.48	0.05	70	250	0.31 × 0.31
BZX79B27	27	26.46	27.54	0.05	80	300	0.31 × 0.31
BZX79B30	30	29.4	30.6	0.05	80	300	0.31 × 0.31
BZX79B33	33	32.34	33.66	0.05	80	325	0.31 × 0.31
BZX79B36	36	35.28	36.72	0.05	90	350	0.31 × 0.31
BZX79B39	39	38.22	39.78	0.05	130	350	0.31 × 0.31
BZX79B43	43	42.14	43.86	0.05	150	375	0.31 × 0.31
BZX79B47	47	46.06	47.94	0.05	170	375	0.31 × 0.31
BZX79B51	51	49.98	52.02	0.05	180	400	0.31 × 0.31
BZX79B56	56	54.88	57.12	0.05	200	425	0.31 × 0.31
BZX79B62	62	60.76	63.24	0.05	215	450	0.31 × 0.31
BZX79B68	68	66.64	69.36	0.05	240	475	0.31 × 0.31
BZX79B75	75	73.5	76.5	0.05	255	500	0.31 × 0.31

 二极管芯片 // 镀银点稳压二极管芯片
 Diode Chips Silver Bump Zener Diode Chips

型 号 Type	V _Z (V)			I _R (μA)	Z _{ZT} (Ω)	Z _{ZK} (Ω)	芯片尺寸 Die Size (mm × mm)	芯片尺寸 Die Size (mm × mm)
	nom	min	max					
BZX79C2V4	2.4	2.2	2.6	50	100	600	0.31 × 0.31	0.25 × 0.25
BZX79C2V7	2.7	2.5	2.9	20	100	600	0.31 × 0.31	0.25 × 0.25
BZX79C3V0	3.0	2.8	3.2	10	95	600	0.31 × 0.31	0.25 × 0.25
BZX79C3V3	3.3	3.1	3.5	5	95	600	0.31 × 0.31	0.25 × 0.25
BZX79C3V6	3.6	3.4	3.8	5	90	600	0.31 × 0.31	0.25 × 0.25
BZX79C3V9	3.9	3.7	4.1	3	90	600	0.31 × 0.31	0.25 × 0.25
BZX79C4V3	4.3	4	4.6	3	90	600	0.31 × 0.31	0.25 × 0.25
BZX79C4V7	4.7	4.4	5	3	80	500	0.31 × 0.31	0.25 × 0.25
BZX79C5V1	5.1	4.8	5.4	2	60	480	0.31 × 0.31	0.25 × 0.25
BZX79C5V6	5.6	5.2	6	1	40	400	0.31 × 0.31	0.25 × 0.25
BZX79C6V2	6.2	5.8	6.6	3	10	150	0.31 × 0.31	0.25 × 0.25
BZX79C6V8	6.8	6.4	7.2	2	15	80	0.31 × 0.31	0.25 × 0.25
BZX79C7V5	7.5	7	7.9	1	15	80	0.31 × 0.31	0.25 × 0.25
BZX79C8V2	8.2	7.7	8.7	0.7	15	80	0.31 × 0.31	0.25 × 0.25
BZX79C9V1	9.1	8.5	9.6	0.5	15	100	0.31 × 0.31	0.25 × 0.25
BZX79C10	10	9.4	10.6	0.2	20	150	0.31 × 0.31	0.25 × 0.25
BZX79C11	11	10.4	11.6	0.1	20	150	0.31 × 0.31	0.25 × 0.25
BZX79C12	12	11.4	12.7	0.1	25	150	0.31 × 0.31	0.25 × 0.25
BZX79C13	13	12.4	14.1	0.1	30	170	0.31 × 0.31	0.25 × 0.25
BZX79C15	15	13.8	15.6	0.05	30	200	0.31 × 0.31	0.25 × 0.25
BZX79C16	16	15.3	17.1	0.05	40	200	0.31 × 0.31	0.25 × 0.25
BZX79C18	18	16.8	19.1	0.05	45	225	0.31 × 0.31	0.25 × 0.25
BZX79C20	20	18.8	21.2	0.05	55	225	0.31 × 0.31	0.25 × 0.25
BZX79C22	22	20.8	23.3	0.05	55	250	0.31 × 0.31	0.25 × 0.25
BZX79C24	24	22.8	25.6	0.05	70	250	0.31 × 0.31	0.25 × 0.25
BZX79C27	27	25.1	28.9	0.05	80	300	0.31 × 0.31	0.25 × 0.25
BZX79C30	30	28	32	0.05	80	300	0.31 × 0.31	
BZX79C33	33	31	35	0.05	80	325	0.31 × 0.31	
BZX79C36	36	34	38	0.05	90	350	0.31 × 0.31	
BZX79C39	39	37	41	0.05	130	350	0.31 × 0.31	
BZX79C43	43	40	46	0.05	150	375	0.31 × 0.31	
BZX79C47	47	44	50	0.05	170	375	0.31 × 0.31	
BZX79C51	51	48	54	0.05	180	400	0.31 × 0.31	
BZX79C56	56	52	60	0.05	200	425	0.31 × 0.31	
BZX79C62	62	58	66	0.05	215	450	0.31 × 0.31	
BZX79C68	68	64	72	0.05	240	475	0.31 × 0.31	
BZX79C75	75	70	79	0.05	255	500	0.31 × 0.31	

5"芯片尺寸0.31 × 0.31; 4"芯片尺寸0.25 × 0.25, 后缀S.

二极管芯片 // 5" TVS二极管芯片
 Diode Chips 5" TVS Diode Chips

型 号 Type	V _{RWM} (V)	V _R (V)		V _C (V)	I _{PP} (A)	I _R (μA)	芯片尺寸 Die Size (mm × mm)
		min	max				
5T035N05V0	5	6	8	20	20	1	0.35 × 0.35
5T035P05V0	-5	-6	-8	-25	-20	-1	0.35 × 0.35
5T044N05V0	5	6	8	25	25	1	0.44 × 0.44
5T044P05V0	-5	-6	-8	-20	-25	-1	0.44 × 0.44
5T035N12V0	12	13.3	16	30	10	1	0.35 × 0.35
5T035P12V0	-12	-13.3	-16	-30	-10	-1	0.35 × 0.35
5T044N12V0	12	13.3	16	30	15	1	0.44 × 0.44
5T044P12V0	-12	-13.3	-16	-30	-15	-1	0.44 × 0.44

 二极管芯片 // 3000W SMDJ系列TVS二极管芯片(4")
 Diode Chips 3000W SMDJ Series TVS Diode Chips (4")

型 号 Type		V _{RWM} (V)	V _R (V)		V _C (V)	I _{PP} (A)	I _R (μA)	芯片尺寸 Die Size (mm × mm)
(Uni)	(Bi)		min	max				
SMDJ8.0A	SMDJ8.0CA	8	8.89	9.83	13.6	220.6	50	4.0 × 4.0
SMDJ8.5A	SMDJ8.5CA	8.5	9.44	10.4	14.4	208.3	20	4.0 × 4.0
SMDJ9.0A	SMDJ9.0CA	9	10	11.1	15.4	194.8	10	4.0 × 4.0
SMDJ10A	SMDJ10CA	10	11.1	12.3	17	176.5	5	4.0 × 4.0
SMDJ11A	SMDJ11CA	11	12.2	13.5	18.2	164.8	2	4.0 × 4.0
SMDJ12A	SMDJ12CA	12	13.3	14.7	19.9	150.8	2	4.0 × 4.0
SMDJ13A	SMDJ13CA	13	14.4	15.9	21.5	139.5	2	4.0 × 4.0
SMDJ14A	SMDJ14CA	14	15.6	17.2	23.2	129.3	2	4.0 × 4.0
SMDJ15A	SMDJ15CA	15	16.7	18.5	24.4	123	2	4.0 × 4.0
SMDJ16A	SMDJ16CA	16	17.8	19.7	26	115.4	2	4.0 × 4.0
SMDJ17A	SMDJ17CA	17	18.9	20.9	27.6	108.7	2	4.0 × 4.0
SMDJ18A	SMDJ18CA	18	20	22.1	29.2	102.7	2	4.0 × 4.0
SMDJ20A	SMDJ20CA	20	22.2	24.5	32.4	92.6	2	4.0 × 4.0
SMDJ22A	SMDJ22CA	22	24.4	26.9	35.5	84.5	2	4.0 × 4.0
SMDJ24A	SMDJ24CA	24	26.7	29.5	38.9	77.1	2	4.0 × 4.0
SMDJ26A	SMDJ26CA	26	28.9	31.9	42.1	71.3	2	4.0 × 4.0
SMDJ28A	SMDJ28CA	28	31.1	34.4	45.4	66.1	2	4.0 × 4.0
SMDJ30A	SMDJ30CA	30	33.3	36.8	48.4	62	2	4.0 × 4.0
SMDJ33A	SMDJ33CA	33	36.7	40.6	53.3	56.3	2	4.0 × 4.0
SMDJ36A	SMDJ36CA	36	40	44.2	58.1	51.6	2	4.0 × 4.0
SMDJ40A	SMDJ40CA	40	44.4	49.1	64.5	46.5	2	4.0 × 4.0
SMDJ43A	SMDJ43CA	43	47.8	52.8	69.4	43.2	2	4.0 × 4.0
SMDJ45A	SMDJ45CA	45	50	55.3	72.7	41.3	2	4.0 × 4.0
SMDJ48A	SMDJ48CA	48	53.3	58.9	77.4	38.8	2	4.0 × 4.0
SMDJ51A	SMDJ51CA	51	56.7	62.7	82.4	36.4	2	4.0 × 4.0
SMDJ54A	SMDJ54CA	54	60	66.3	87.1	34.4	2	4.0 × 4.0
SMDJ58A	SMDJ58CA	58	64.4	71.2	93.6	32.1	2	4.0 × 4.0
SMDJ60A	SMDJ60CA	60	66.7	73.7	96.8	31	2	4.0 × 4.0
SMDJ64A	SMDJ64CA	64	71.1	78.6	103	29.1	2	4.0 × 4.0
SMDJ70A	SMDJ70CA	70	77.8	86	113	26.5	2	4.0 × 4.0
SMDJ75A	SMDJ75CA	75	83.3	92.1	121	24.8	2	4.0 × 4.0
SMDJ78A	SMDJ78CA	78	86.7	95.8	126	23.8	2	4.0 × 4.0
SMDJ85A	SMDJ85CA	85	94.4	104	137	21.9	2	4.0 × 4.0
SMDJ90A	SMDJ90CA	90	100	111	146	20.5	2	4.0 × 4.0
SMDJ100A	SMDJ100CA	100	111	123	162	18.5	2	4.0 × 4.0
SMDJ110A	SMDJ110CA	110	122	135	177	16.9	2	4.0 × 4.0
SMDJ120A	SMDJ120CA	120	133	147	193	15.5	2	4.0 × 4.0
SMDJ130A	SMDJ130CA	130	144	159	209	14.4	2	4.0 × 4.0
SMDJ150A	SMDJ150CA	150	167	185	243	12.3	2	4.0 × 4.0
SMDJ160A	SMDJ160CA	160	178	197	259	11.6	2	4.0 × 4.0
SMDJ170A	SMDJ170CA	170	189	209	275	10.9	2	4.0 × 4.0

 二极管芯片 // 400W SMAJ系列TVS二极管芯片(4")
 Diode Chips 400W SMAJ Series TVS Diode Chips (4")

型 号 Type		V _{RWM} (V)	V _R (V)		V _C (V)	I _{PP} (A)	I _R (μA)	芯片尺寸 Die Size (mm × mm)
(Uni)	(Bi)		min	max				
SMAJ8.0A	SMAJ8.0CA	8	8.89	9.83	13.6	29.4	50	1.5 × 1.5
SMAJ8.5A	SMAJ8.5CA	8.5	9.44	10.4	14.4	27.8	20	1.5 × 1.5
SMAJ9.0A	SMAJ9.0CA	9	10	11.1	15.4	26	10	1.5 × 1.5
SMAJ10A	SMAJ10CA	10	11.1	12.3	17	23.5	5	1.5 × 1.5
SMAJ11A	SMAJ11CA	11	12.2	13.5	18.2	22	1	1.5 × 1.5
SMAJ12A	SMAJ12CA	12	13.3	14.7	19.9	20.1	1	1.5 × 1.5
SMAJ13A	SMAJ13CA	13	14.4	15.9	21.5	18.6	1	1.5 × 1.5
SMAJ14A	SMAJ14CA	14	15.6	17.2	23.2	17.2	1	1.5 × 1.5
SMAJ15A	SMAJ15CA	15	16.7	18.5	24.4	16.4	1	1.5 × 1.5
SMAJ16A	SMAJ16CA	16	17.8	19.7	26	15.4	1	1.5 × 1.5
SMAJ17A	SMAJ17CA	17	18.9	20.9	27.6	14.5	1	1.5 × 1.5
SMAJ18A	SMAJ18CA	18	20	22.1	29.2	13.7	1	1.5 × 1.5
SMAJ20A	SMAJ20CA	20	22.2	24.5	32.4	12.3	1	1.5 × 1.5
SMAJ22A	SMAJ22CA	22	24.4	26.9	35.5	11.3	1	1.5 × 1.5
SMAJ24A	SMAJ24CA	24	26.7	29.5	38.9	10.3	1	1.5 × 1.5
SMAJ26A	SMAJ26CA	26	28.9	31.9	42.1	9.5	1	1.5 × 1.5
SMAJ28A	SMAJ28CA	28	31.1	34.4	45.4	8.8	1	1.5 × 1.5
SMAJ30A	SMAJ30CA	30	33.3	36.8	48.4	8.3	1	1.5 × 1.5
SMAJ33A	SMAJ33CA	33	36.7	40.6	53.3	7.5	1	1.5 × 1.5
SMAJ36A	SMAJ36CA	36	40	44.2	58.1	6.9	1	1.5 × 1.5
SMAJ40A	SMAJ40CA	40	44.4	49.1	64.5	6.2	1	1.5 × 1.5
SMAJ43A	SMAJ43CA	43	47.8	52.8	69.4	5.8	1	1.5 × 1.5
SMAJ45A	SMAJ45CA	45	50	55.3	72.7	5.5	1	1.5 × 1.5
SMAJ48A	SMAJ48CA	48	53.3	58.9	77.4	5.2	1	1.5 × 1.5
SMAJ51A	SMAJ51CA	51	56.7	62.7	82.4	4.9	1	1.5 × 1.5
SMAJ54A	SMAJ54CA	54	60	66.3	87.1	4.6	1	1.5 × 1.5
SMAJ58A	SMAJ58CA	58	64.4	71.2	93.6	4.3	1	1.5 × 1.5
SMAJ60A	SMAJ60CA	60	66.7	73.7	96.8	4.1	1	1.5 × 1.5
SMAJ64A	SMAJ64CA	64	71.1	78.6	103	3.9	1	1.5 × 1.5
SMAJ70A	SMAJ70CA	70	77.8	86	113	3.5	1	1.5 × 1.5
SMAJ75A	SMAJ75CA	75	83.3	92.1	121	3.3	1	1.5 × 1.5
SMAJ78A	SMAJ78CA	78	86.7	95.8	126	3.2	1	1.5 × 1.5
SMAJ85A	SMAJ85CA	85	94.4	104	137	2.9	1	1.5 × 1.5
SMAJ90A	SMAJ90CA	90	100	111	146	2.7	1	1.5 × 1.5
SMAJ100A	SMAJ100CA	100	111	123	162	2.5	1	1.5 × 1.5
SMAJ110A	SMAJ110CA	110	122	135	177	2.3	1	1.5 × 1.5
SMAJ120A	SMAJ120CA	120	133	147	193	2.1	1	1.5 × 1.5
SMAJ130A	SMAJ130CA	130	144	159	209	1.9	1	1.5 × 1.5
SMAJ150A	SMAJ150CA	150	167	185	243	1.6	1	1.5 × 1.5
SMAJ160A	SMAJ160CA	160	178	197	259	1.5	1	1.5 × 1.5
SMAJ170A	SMAJ170CA	170	189	209	275	1.5	1	1.5 × 1.5
SMAJ180A	SMAJ180CA	180	201	222	292	1.4	1	1.5 × 1.5
SMAJ200A	SMAJ200CA	200	224	247	324	1.2	1	1.5 × 1.5
SMAJ220A	SMAJ220CA	220	246	272	356	1.1	1	1.5 × 1.5
SMAJ250A	SMAJ250CA	250	279	309	405	1	1	1.5 × 1.5

二极管芯片 // 600W SMBJ系列TVS二极管芯片 (4")
 Diode Chips 600W SMBJ Series TVS Diode Chips (4")

型 号 Type		V _{RWM} (V)	V _R (V)		V _C (V)	I _{PP} (A)	I _R (μA)	芯片尺寸 Die Size (mm × mm)
(Uni)	(Bi)		min	max				
SMBJ8.0A	SMBJ8.0CA	8	8.89	9.83	13.6	44.2	50	1.8×1.8
SMBJ8.5A	SMBJ8.5CA	8.5	9.44	10.4	14.4	41.7	20	1.8×1.8
SMBJ9.0A	SMBJ9.0CA	9	10	11.1	15.4	39	10	1.8×1.8
SMBJ10A	SMBJ10CA	10	11.1	12.3	17	35.3	5	1.8×1.8
SMBJ11A	SMBJ11CA	11	12.2	13.5	18.2	33	1	1.8×1.8
SMBJ12A	SMBJ12CA	12	13.3	14.7	19.9	30.2	1	1.8×1.8
SMBJ13A	SMBJ13CA	13	14.4	15.9	21.5	28	1	1.8×1.8
SMBJ14A	SMBJ14CA	14	15.6	17.2	23.2	25.9	1	1.8×1.8
SMBJ15A	SMBJ15CA	15	16.7	18.5	24.4	24.6	1	1.8×1.8
SMBJ16A	SMBJ16CA	16	17.8	19.7	26	23.1	1	1.8×1.8
SMBJ17A	SMBJ17CA	17	18.9	20.9	27.6	21.8	1	1.8×1.8
SMBJ18A	SMBJ18CA	18	20	22.1	29.2	20.6	1	1.8×1.8
SMBJ20A	SMBJ20CA	20	22.2	24.5	32.4	18.6	1	1.8×1.8
SMBJ22A	SMBJ22CA	22	24.4	26.9	35.5	16.9	1	1.8×1.8
SMBJ24A	SMBJ24CA	24	26.7	29.5	38.9	15.5	1	1.8×1.8
SMBJ26A	SMBJ26CA	26	28.9	31.9	42.1	14.3	1	1.8×1.8
SMBJ28A	SMBJ28CA	28	31.1	34.4	45.4	13.3	1	1.8×1.8
SMBJ30A	SMBJ30CA	30	33.3	36.8	48.4	12.4	1	1.8×1.8
SMBJ33A	SMBJ33CA	33	36.7	40.6	53.3	11.3	1	1.8×1.8
SMBJ36A	SMBJ36CA	36	40	44.2	58.1	10.4	1	1.8×1.8
SMBJ40A	SMBJ40CA	40	44.4	49.1	64.5	9.3	1	1.8×1.8
SMBJ43A	SMBJ43CA	43	47.8	52.8	69.4	8.7	1	1.8×1.8
SMBJ45A	SMBJ45CA	45	50	55.3	72.7	8.3	1	1.8×1.8
SMBJ48A	SMBJ48CA	48	53.3	58.9	77.4	7.8	1	1.8×1.8
SMBJ51A	SMBJ51CA	51	56.7	62.7	82.4	7.3	1	1.8×1.8
SMBJ54A	SMBJ54CA	54	60	66.3	87.1	6.9	1	1.8×1.8
SMBJ58A	SMBJ58CA	58	64.4	71.2	93.6	6.5	1	1.8×1.8
SMBJ60A	SMBJ60CA	60	66.7	73.7	96.8	6.2	1	1.8×1.8
SMBJ64A	SMBJ64CA	64	71.1	78.6	103	5.9	1	1.8×1.8
SMBJ70A	SMBJ70CA	70	77.8	86	113	5.3	1	1.8×1.8
SMBJ75A	SMBJ75CA	75	83.3	92.1	121	5	1	1.8×1.8
SMBJ78A	SMBJ78CA	78	86.7	95.8	126	4.8	1	1.8×1.8
SMBJ85A	SMBJ85CA	85	94.4	104	137	4.4	1	1.8×1.8
SMBJ90A	SMBJ90CA	90	100	111	146	4.1	1	1.8×1.8
SMBJ100A	SMBJ100CA	100	111	123	162	3.7	1	1.8×1.8
SMBJ110A	SMBJ110CA	110	122	135	177	3.4	1	1.8×1.8
SMBJ120A	SMBJ120CA	120	133	147	193	3.1	1	1.8×1.8
SMBJ130A	SMBJ130CA	130	144	159	209	2.9	1	1.8×1.8
SMBJ150A	SMBJ150CA	150	167	185	243	2.5	1	1.8×1.8
SMBJ160A	SMBJ160CA	160	178	197	259	2.3	1	1.8×1.8
SMBJ170A	SMBJ170CA	170	189	209	275	2.2	1	1.8×1.8
SMBJ180A	SMBJ180CA	180	201	222	292	2.1	1	1.8×1.8
SMBJ200A	SMBJ200CA	200	224	247	324	1.9	1	1.8×1.8
SMBJ220A	SMBJ220CA	220	246	272	356	1.7	1	1.8×1.8
SMBJ250A	SMBJ250CA	250	279	309	405	1.5	1	1.8×1.8

 二极管芯片 // 1500W SMCJ系列TVS二极管芯片 (4")
 Diode Chips 1500W SMCJ Series TVS Diode Chips (4")

型 号 Type		V _{RWM} (V)	V _R (V)		V _C (V)	I _{PP} (A)	I _R (μA)	芯片尺寸 Die Size (mm × mm)
(Uni)	(Bi)		min	max				
SMCJ8.0A	SMCJ8.0CA	8	8.89	9.83	13.6	110.3	50	2.9×2.9
SMCJ8.5A	SMCJ8.5CA	8.5	9.44	10.4	14.4	104.2	20	2.9×2.9
SMCJ9.0A	SMCJ9.0CA	9	10	11.1	15.4	97.4	10	2.9×2.9
SMCJ10A	SMCJ10CA	10	11.1	12.3	17	88.3	5	2.9×2.9
SMCJ11A	SMCJ11CA	11	12.2	13.5	18.2	82.5	1	2.9×2.9
SMCJ12A	SMCJ12CA	12	13.3	14.7	19.9	75.4	1	2.9×2.9
SMCJ13A	SMCJ13CA	13	14.4	15.9	21.5	69.8	1	2.9×2.9
SMCJ14A	SMCJ14CA	14	15.6	17.2	23.2	64.7	1	2.9×2.9
SMCJ15A	SMCJ15CA	15	16.7	18.5	24.4	61.5	1	2.9×2.9
SMCJ16A	SMCJ16CA	16	17.8	19.7	26	57.7	1	2.9×2.9
SMCJ17A	SMCJ17CA	17	18.9	20.9	27.6	54.4	1	2.9×2.9
SMCJ18A	SMCJ18CA	18	20	22.1	29.2	51.4	1	2.9×2.9
SMCJ20A	SMCJ20CA	20	22.2	24.5	32.4	46.3	1	2.9×2.9
SMCJ22A	SMCJ22CA	22	24.4	26.9	35.5	42.3	1	2.9×2.9
SMCJ24A	SMCJ24CA	24	26.7	29.5	38.9	38.6	1	2.9×2.9
SMCJ26A	SMCJ26CA	26	28.9	31.9	42.1	35.7	1	2.9×2.9
SMCJ28A	SMCJ28CA	28	31.1	34.4	45.4	33.1	1	2.9×2.9
SMCJ30A	SMCJ30CA	30	33.3	36.8	48.4	31	1	2.9×2.9
SMCJ33A	SMCJ33CA	33	36.7	40.6	53.3	28.2	1	2.9×2.9
SMCJ36A	SMCJ36CA	36	40	44.2	58.1	25.9	1	2.9×2.9
SMCJ40A	SMCJ40CA	40	44.4	49.1	64.5	23.3	1	2.9×2.9
SMCJ43A	SMCJ43CA	43	47.8	52.8	69.4	21.7	1	2.9×2.9
SMCJ45A	SMCJ45CA	45	50	55.3	72.7	20.6	1	2.9×2.9
SMCJ48A	SMCJ48CA	48	53.3	58.9	77.4	19.4	1	2.9×2.9
SMCJ51A	SMCJ51CA	51	56.7	62.7	82.4	18.2	1	2.9×2.9
SMCJ54A	SMCJ54CA	54	60	66.3	87.1	17.3	1	2.9×2.9
SMCJ58A	SMCJ58CA	58	64.4	71.2	93.6	16.1	1	2.9×2.9
SMCJ60A	SMCJ60CA	60	66.7	73.7	96.8	15.5	1	2.9×2.9
SMCJ64A	SMCJ64CA	64	71.1	78.6	103	14.6	1	2.9×2.9
SMCJ70A	SMCJ70CA	70	77.8	86	113	13.3	1	2.9×2.9
SMCJ75A	SMCJ75CA	75	83.3	92.1	121	12.4	1	2.9×2.9
SMCJ78A	SMCJ78CA	78	86.7	95.8	126	11.9	1	2.9×2.9
SMCJ85A	SMCJ85CA	85	94.4	104	137	11	1	2.9×2.9
SMCJ90A	SMCJ90CA	90	100	111	146	10.3	1	2.9×2.9
SMCJ100A	SMCJ100CA	100	111	123	162	9.3	1	2.9×2.9
SMCJ110A	SMCJ110CA	110	122	135	177	8.5	1	2.9×2.9
SMCJ120A	SMCJ120CA	120	133	147	193	7.8	1	2.9×2.9
SMCJ130A	SMCJ130CA	130	144	159	209	7.2	1	2.9×2.9
SMCJ150A	SMCJ150CA	150	167	185	243	6.2	1	2.9×2.9
SMCJ160A	SMCJ160CA	160	178	197	259	5.8	1	2.9×2.9
SMCJ170A	SMCJ170CA	170	189	209	275	5.5	1	2.9×2.9
SMCJ180A	SMCJ180CA	180	201	222	292	5.1	1	2.9×2.9
SMCJ200A	SMCJ200CA	200	224	247	324	4.6	1	2.9×2.9
SMCJ220A	SMCJ220CA	220	246	272	356	4.2	1	2.9×2.9

集成电路芯片 // IC Chips

三端稳压电路芯片(5")
Three-Terminal Voltage Regulator Chips(5")

型 号 Type	P _D (W)	I _{CC} (mA)	I _{OUT} (A)	V _{IN} (V)	V _{OUT} (V)	T _a (°C)	芯片尺寸 Die Size (mm×mm)
7805	15	7.3	1.5	30	4.9-5.1	0-70	1.39×1.72
7806	15	7.3	1.5	30	5.9-6.1	0-70	1.39×1.72
7808	15	7.3	1.5	30	7.85-8.15	0-70	1.39×1.72
7809	15	7.3	1.5	30	8.85-9.15	0-70	1.39×1.72
7812	15	7.3	1.5	30	11.8-12.2	0-70	1.39×1.72

电力电子器件 // Power Electronic Devices

ZP型普通整流管
Standard Diodes

型 号 Type	I _{F(AV)} (A)	I _{FSM} (kA)	V _{RRM} (V)	I _{RRM} (mA)	V _{FM@I_{FM}}		T _{jm} (°C)	F (kN)	R _{thj-c} (°C/W)	外形 Outline
					(V)	(A)				
ZP500	500	7.5	400-1400	20	1.8	1500	150	3.2-3.9	0.095	
ZP400	400	6	1400-2000	20	1.8	1200	150	3.2-3.9	0.095	
ZP700	700	10.5	400-1400	30	1.8	2000	150	9-11	0.055	
ZP600	600	9	1400-2000	30	1.8	1800	150	9-11	0.055	
ZP500	500	7.5	2000-2600	30	2	1500	150	9-11	0.055	
ZP1500	1500	22.5	400-1400	40	1.8	3000	150	14-17	0.037	
ZP1100	1100	16.5	1400-2000	40	2	3000	150	14-17	0.037	
ZP900	900	13.5	2000-2600	40	2	2700	150	14-17	0.037	
ZP800	800	12	2600-3400	40	2	2400	150	14-17	0.037	
ZP600	600	9	3600-4500	40	2	1800	150	14-17	0.037	
ZP2400	2400	36	600-1400	80	1.6	3000	150	22-26	0.023	
ZP1800	1800	27	1400-2000	80	1.6	3000	150	22-26	0.023	
ZP1600	1600	24	2000-2600	80	1.8	3000	150	22-26	0.023	
ZP1500	1500	22.5	2600-3400	80	1.8	3000	150	22-26	0.023	
ZP1200	1200	18	3600-4500	80	2	3000	150	22-26	0.023	
ZP2500	2500	37.5	1400-2000	100	1.5	3000	150	27-34	0.016	
ZP2000	2000	30	2000-2600	100	1.6	3000	150	27-34	0.016	
ZP3000	3000	45	1400-2000	120	1.5	4000	150	30-36	0.012	
ZP2500	2500	37.5	2000-2600	120	1.6	4000	150	30-36	0.012	
ZP6000	6000	90	600-1400	150	1.5	5000	150	32-40	0.01	
ZP5000	5000	75	1400-2000	150	1.6	5000	150	32-40	0.01	
ZP4000	4000	60	2000-2600	150	1.8	5000	150	32-40	0.01	
ZP3900	3900	58.5	2600-3400	150	1.8	5000	150	32-40	0.01	
ZP2900	2900	43.5	3600-4500	150	2	5000	150	32-40	0.01	

电力电子器件 // Power Electronic Devices

ZK型快速整流管
Fast Recovery Diodes

型 号 Type	I _{F(AV)} (A)	I _{FSM} (kA)	V _{RRM} (V)	I _{RRM} (mA)	V _{FM@I_{FM}}		t _{rr} (μs)	T _{jm} (°C)	F (kN)	R _{thj-c} (°C/W)	外形 Outline
					(V)	(A)					
ZK200	200	3	500-2500	15	2.2	600	5	150	3.2-3.9	0.095	
ZK300	300	4.5	500-2500	25	2.2	900	5	150	9-11	0.055	
ZK400	400	6	500-2500	25	2.2	1200	5	150	9-11	0.055	
ZK500	500	7.5	500-2500	35	2.2	1500	5	150	14-17	0.037	
ZK600	600	9	500-2500	35	2.2	1800	5	150	14-17	0.037	
ZK800	800	12	500-2500	55	2.2	2400	10	150	22-26	0.023	
ZK1000	1000	15	500-2500	55	2.2	3000	10	150	22-26	0.023	

电力电子器件 // Power Electronic Devices

普通晶闸管
Phase Control Thyristors

型 号 Type	I _{T(AV)} (A)	V _{DRM/V_{RRM}} (V)	I _{DRM/I_{RRM}} (mA)	V _{TM} (V)	V _{GT} (V)	I _{GT} (mA)	dv/dt (V/μs)	R _{thj-c} (°C/W)	T _{jm} (°C)	F (kN)	外形 Outline
KP400	400	400-1400	20	1.8	3	40-150	1000	0.095	125	3.2-3.9	
KP300	300	1400-2000	20	1.8	3	40-150	1000	0.095	125	3.2-3.9	
KP600	600	400-1400	30	2.2	3	40-150	1000	0.055	125	9-11	
KP500	500	1400-2000	30	2	3	40-150	1000	0.055	125	9-11	
KP400	400	2000-2600	30	2	3.5	40-150	1000	0.055	125	9-11	
KP300	300	2600-3400	30	2.8	3.5	40-180	1000	0.055	125	9-11	
KP200	200	3600-4000	40	3.2	3.5	40-200	1000	0.055	125	9-11	
KP900	900	400-1400	40	1.8	3	40-150	1000	0.037	125	14-17	
KP800	800	1400-2000	40	1.8	3	40-150	1000	0.037	125	14-17	
KP600	600	2000-2600	50	2.2	3	40-150	1000	0.037	125	14-17	
KP500	500	2600-3400	50	2.2	3.5	40-150	1000	0.037	125	14-17	
KP400	400	3600-4500	60	2.8	3.5	40-200	1000	0.037	125	14-17	
KP1600	1600	400-1400	60	1.6	3	40-150	1000	0.023	125	22-26	
KP1500	1500	1400-2000	80	2	3	40-150	1000	0.023	125	22-26	
KP1300	1300	2000-2600	80	1.5	3	40-150	1000	0.023	125	22-26	
KP1000	1000	2600-3400	80	1.6	3	40-150	1000	0.023	125	22-26	
KP800	800	3600-4500	100	2	3.5	40-150	1000	0.023	125	22-26	
KP1800	1800	1400-2000	120	1.6	2.5	50-160	1000	0.016	125	27-34	
KP1600	1600	2000-3000	120	1.8	2.5	50-160	1000	0.016	125	27-34	
KP1500	1500	2600-3400	120	2	2.5	50-180	1000	0.016	125	27-34	
KP1000	1000	3600-4500	120	2.8	3	50-200	1000	0.016	125	27-34	
KP2500	2500	1400-2000	150	1.6	2.5	50-160	1000	0.012	125	30-36	
KP2000	2000	2000-3000	150	1.7	2.5	50-160	1000	0.012	125	30-36	
KP1800	1800	2600-3400	150	2	2.5	50-180	1000	0.012	125	30-36	
KP3000	3000	1400-2000	180	1.4	2.5	50-160	1000	0.01	125	32-40	
KP2500	2500	2000-3000	180	1.5	2.5	50-160	1000	0.01	125	32-40	
KP2300	2300	2600-3400	180	1.6	2.5	50-180	1000	0.01	125	32-40	
KP1650	1650	3600-4500	200	2	3	50-200	1000	0.01	125	32-40	
KP3500	3500	2000-2600	250	1.4	2.5	50-160	1000	0.008	125	45-55	
KP3200	3200	2600-3400	250	1.5	2.5	50-180	1000	0.008	125	45-55	
KP3000	3000	3600-4500	250	1.6	3	50-200	1000	0.008	125	45-55	

电力电子器件 // Power Electronic Devices

快速晶闸管
Inverter Thyristors

型 号 Type	I _{T(AV)} (A)	V _{DRM/V_{RRM}} (V)	I _{DRM/I_{RRM}} (mA)	V _{TM} (V)	V _{GT} (V)	I _{GT} (mA)	t _a (μs)	R _{thj-c} (°C/W)	T _{jm} (°C)	F (kN)	外形 Outline
KK200	200	600-2000	30	3	3	150	30	0.055	125	9-11	
KK300	300	600-2000	30	3	3	150	30	0.055	125	9-11	
KK400	400	600-2000	40	3	3	150	40	0.037	125	14-17	
KK500	500	600-2000	40	3	3	150	40	0.037	125	14-17	
KK600	600	600-2000	40	3	3	150	40	0.037	125	14-17	
KK800	800	600-2000	70	3	3	200	50	0.023	125	22-26	
KK1000	1000	600-2000	70	3	3	200	50	0.023	125	22-26	
KK1200	1200	600-2000	80	3.2	3	200	60	0.018	125	27-34	
KK1500	1500	600-2000	100	3.2	3	200	60	0.018	125	27-34	
KK1800	1800	600-2000	100	3.2	3	200	60	0.016	125	27-34	
KK2000	2000	600-2000	100	3.2	3	250	60	0.012	125	30-36	
KK2000	2000	2100-2500	100	3.2	3	250	70	0.012	125	30-36	
KK2000	2000	2600-3000	120	3.2	3	250	100	0.012	125	30-36	
KK2500	2500	600-2000	120	3.2	3	250	60	0.01	125	32-40	
KK2500	2500	2100-2500	150	3.2	3	250	70	0.01	125	32-40	
KK3000	3000	2000-2500	200	3.2	3	250	80	0.008	125	45-55	

电力电子器件 // 整流管模块
Power Electronic Devices Diode Modules

型号 Type	$I_{F(AV)}$ @85°C (A)	V_{RRM} (V)	I_{RRM} (max) (mA)	I_{FSM} (A)	V_{FM} (max) (V)	R_{thj-c} (max) (°C/W)	V_{ISO} (min) (V)	T_{jm} (°C)	外形 Outline
MDC MDK MDA	130A	800-2000	20	2600	1.5	0.16	2500	150	
	160A	800-2000	20	3200	1.5	0.16	2500	150	
	200A	800-2500	30	4000	1.6	0.12	2500	150	
	250A	800-2500	30	5000	1.6	0.12	2500	150	
	300A	800-2500	30	5500	1.5	0.1	2500	150	
	400A*	800-2500	35	5500	1.6	0.1	2500	150	
	400A	800-2500	40	8000	1.5	0.08	2500	150	
	500A*	800-2500	40	10000	1.6	0.08	2500	150	
	500A	800-2500	45	10000	1.6	0.07	2500	150	
	600A*	800-2500	45	12000	1.6	0.07	2500	150	
	600A	800-2500	50	12000	1.6	0.06	2500	150	
	800A	800-2500	50	13000	1.6	0.06	2500	150	
	800A*	800-2500	50	13000	1.6	0.054	2500	150	
	1000A*	800-2500	50	16000	1.6	0.054	2500	150	

*:水冷水冷却

电力电子器件 // 晶闸管/整流管混合模块
Power Electronic Devices Thyristor/Diode Modules

型号 Type	$I_T(AV)$ @85°C (A)	V_{RRM} V_{DRM} (V)	I_{RRM} I_{DRM} (max) (mA)	V_{TM} V_{FM} (max) (V)	I_{GT} @25°C (max) (mA)	V_{GT} @25°C (max) (V)	dv/dt (min) (V/μs)	R_{thj-c} (max) (°C/W)	V_{ISO} (min) (V)	T_{jm} (°C)	外形 Outline
MFC MFX MFK MFA	130A	800-2500	20	1.75/1.5	140	2.8	800	0.16	2500	125	
	160A	800-2500	20	1.75/1.5	140	2.8	800	0.16	2500	125	
	200A	800-2500	30	1.9/1.6	150	2.8	800	0.12	2500	125	
	250A	800-2500	30	1.9/1.6	150	2.8	800	0.12	2500	125	
	300A	800-1800	30	1.6/1.5	150	2.8	800	0.1	2500	125	
	400A*	800-2500	35	1.9/1.6	150	2.8	800	0.1	2500	125	
	400A	800-2500	40	1.7/1.5	150	2.8	800	0.08	2500	125	
	500A*	800-2500	40	1.9/1.6	150	2.8	800	0.08	2500	125	
	500A	800-2500	45	1.9/1.6	150	2.8	800	0.07	2500	125	
	600A*	800-2500	45	1.9/1.6	150	2.8	800	0.07	2500	125	
	600A	800-2500	50	1.9/1.6	150	2.8	800	0.06	2500	125	
	800A	800-2500	50	1.8/1.6	150	2.8	800	0.06	2500	125	
	800A*	800-2500	50	1.9/1.6	150	2.8	800	0.054	2500	125	

*:水冷水冷却

电力电子器件 // 晶闸管模块
Power Electronic Devices Thyristor Modules

型号 Type	$I_T(AV)$ @85°C (A)	V_{RRM} V_{DRM} (V)	I_{RRM} I_{DRM} (max) (mA)	V_{TM} (max) (V)	I_{GT} @25°C (max) (mA)	V_{GT} @25°C (max) (V)	dv/dt (min) (V/μs)	R_{thj-c} (max) (°C/W)	V_{ISO} (min) (V)	T_{jm} (°C)	外形 Outline
MTC MTK MTX MTA	130A	800-2500	20	1.75	140	2.8	500	0.16	2500	125	
	160A	800-2500	20	1.75	140	2.8	500	0.16	2500	125	
	200A	800-2500	30	1.9	150	2.8	500	0.12	2500	125	
	250A	800-2500	30	1.9	150	2.8	800	0.12	2500	125	
	300A	800-1800	30	1.6	150	2.8	800	0.1	2500	125	
	400A*	800-2500	35	1.9	150	2.8	800	0.1	2500	125	
	400A	800-2500	40	1.7	150	2.8	800	0.08	2500	125	
	500A*	800-2500	40	1.9	150	2.8	800	0.08	2500	125	
	500A	800-2500	45	1.9	150	2.8	800	0.07	2500	125	
	600A*	800-2500	45	1.9	150	2.8	800	0.07	2500	125	
	600A	800-2500	50	1.9	150	2.8	800	0.06	2500	125	
	800A	800-2500	50	1.8	150	2.8	800	0.06	2500	125	
	800A*	800-2500	50	1.9	150	2.8	800	0.054	2500	125	

*:水冷水冷却

客户

Customer



合作伙伴

Partners

